

ADVERTISEMENT FOR BIDS

Notice is hereby given that sealed bids will be received by the Adams County Board of Supervisors for the purchase, from the lowest and best bidder, of the following item as needed, for the Adams County Road Department, for a New 2025 or greater Compact Track Loader. Used, demonstrator, or discounted models are unacceptable. Bidders shall include printed literature for the equipment offered.

Bids must be received by 10:00 A.M., Thursday, October 2, 2025 at the County Administration Building, 314 State Street, Natchez, Mississippi, at which time bids will be opened.

Bids submitted with qualifications or exceptions will not be considered.

All bids are to be SEALED, PLAINLY ADDRESSED TO THE ADAMS COUNTY BOARD OF SUPERVISORS, and outside of envelope containing bids should be marked; "BID ON (# Item Bidding On)".

Bids may be hand delivered to 314 State Street, Natchez, Mississippi or mailed to the County Administration Building, Natchez, Mississippi 39120.

Bid prices are to be firm and not subject to change during the period specified above.

The Board of Supervisors reserves the right to waive informalities and to reject any and all bids.

DE'NEEN PRICE
PURCHASE CLERK
601-445-7941

PUBLICATION DATES:
September 17, 2025
September 24, 2025

Bid Opening: October 2, 2025

Specifications for Compact Track Loader Adams County Road Department

Equipment offered for consideration must be new 2025 or greater. Used, demonstrator, or discounted models are unacceptable. Bidders shall include printed literature for the equipment offered.

The following specifications are considered minimum acceptable.

Engine

- Four (4) cylinder, turbo charge, intercooled or after cooled diesel engine
- Engine shall be certified to meet final tier 4 missions standards
- Engine maximum new power shall be at least 117HP
- Machine shall require diesel exhaust fluid and can be filled from ground level

Weight

- Minimum machine weight 12,300 LBS

Operating Specifications

- Minimum tipping load at 10,500 LBS
- Minimum height to hinge pin 11' and have vertical lift
- Minimum bucket breakout force of 9,500 LBS and boom breakout force of 6,422 LBS

Hydraulics

- Hydraulic pump shall have minimum 23 GPM standard flow and 40 GPM high flow
- Hydraulic system pressure minimum 3500 PSI standard flow and 4000PSI high flow
- Hydraulic tank shall be no less than 6.9 Gallons
- Hydraulic controls shall be electro hydraulic joystick controls
- Machine shall have a hydraulic sight level that can be checked from outside the machine

Powertrain

- Shall be hydrostatic drive with twow (2) variable displacement, axial piston pumps
- Machine shall have a two (2) speed transmission
- Minimum speed in low range 5.2 MPH
- Minimum speed in high range 7.8 MPH

Electrical

- Machine shall have a battery with a minimum 950 CCA
- Machine shall have a 12-volt system with a 100 AMP alternator rating

Brakes

- Machine shall have braking system with integral, automatic, spring applied, hydraulically released wet-disc

Undercarriage

- Machine shall have rubber tracks that are a minimum of 17.5" S wide
- Tracks shall be rubber with steel inserts
- Machine shall have a minimum of five (5) triple flange steel bottom rollers
- Machine shall have a minimum of two (2) double flange track idlers

Operators Station

- Machine shall be equipped with ROPS/FOPS protection
- Cab must have air conditioning and heat
- Machine shall have a cloth heated and cooled air suspension seat
- Cab shall have beverage holder, 2" seatbelt, am/fm radio with bluetooth, rearview mirror, keyless start system with integrated anti-theft system, 12-volt power port, and pull-down lap bar
- Machine shall have a rearview camera

General Specifications

- Machine shall have LED light package
- Machine shall have a hydraulic attachment connection for attachments
- Machine shall have severe-duty front cab window with wipers
- Machine shall have environmental drains for all fluid reservoirs
- Machine shall have an in-cab boom lockout system to secure before exiting seat
- Machine shall have a minimum fuel tank capacity of 35 gallons
- Machine shall have a minimum 84" general purpose bucket with Boce
- Machine shall have gauges for: engine coolant temperature, hydraulic oil temperature, and engine oil pressure
- Machine shall have digital read outs for engine RPMS, transmission, hour meter, fuel level and def level or equal
- Machine shall have a 72" brush mower, with a minimum cutting height of 2.5 inches, minimum cutting width of 72 inches, minimum of 3 blades, have a maximum cutting capacity of 8 inches (tree size) mower weight shall be no less than 1750 LBS and hydraulic high glow of 32-39 GPMS and 3400 PSI
- Machine shall have an 84" grapple bucket with dual grapple and a grapple weight minimum of 1150 LBS, and maximum hydraulic pressure of 3400 PSI

- The bid machine shall be equipped with OEM provided wireless communication system capable of monitoring and communication machine location, fuel burn, and other machine performance data

Warranty

- Full machine warranty for duration of the lease, including any and all travel time and millage

Buyback

- 36-month machine buybacks must be provided

Other

- Bidder shall have a certified parts and service center located within 50 miles of Natchez, MS, Adams, County
- Must give estimate time of delivery
- Cost must include delivery to one of the county barns

Name of Company _____

Address of Company _____

Contact Number _____

Location of Service Center _____

Name of Seller _____

Signature of Seller _____